PROFLUID™ VELOCITY

TECHNICAL DATA SHEET

ProFluid™ Velocity SAE 10W-40, SAE 20W-50

Synthetic Blend Motor Oil, API SQ

ProFluid™ Velocity SAE 10W-40 and SAE 20W-50 are high-quality synthetic blend motor oils designed specifically for today's gasoline engines that require the latest industry standards, including API SQ, API SP, API SN Plus, and API SN. These motor oils provide outstanding protection and efficiency for a wide range of passenger cars, SUVs, and light trucks, ensuring optimal engine performance under diverse driving conditions.

ProFluid™ Velocity oils are expertly blended from a combination of high-performance synthetic and Group II paraffinic base oils, together with an advanced additive system. This sophisticated formulation is specifically engineered to deliver exceptional protection for high-compression gasoline direct injection engines.

- Meets and exceeds industry requirements for modern engine designs, including turbocharged and direct injection systems
- Ensures excellent engine cleanliness and minimizes sludge formation, even under severe driving conditions
- Provides enhanced oxidative stability for longer oil life and sustained engine performance
- Improved low-speed pre-ignition (LSPI) protection, safeguarding engines from premature damage

ProFluid™ Velocity Motor Oils are an ideal choice for drivers seeking reliable, state-of-the-art lubrication that preserves engine efficiency, reduces emissions, and provides peace of mind through enhanced protection and performance.

Typical Properties

Physical	Unit	Test Method	10W-40	20W-50
Appearance, Visual	—	Visual	Amber, Transparent, Liquid	
Viscosity@40°C	cSt	ASTM D445	92.85	148.95
Viscosity@100°C	cSt	ASTM D445	14.0	18.0
Viscosity Index	—	ASTM D2270	155	135
CCS Apparent Viscosity	cP	ASTM D5293	5,800@-25°C	6,800@-15°C
MRV Apparent Viscosity	cP	ASTM D4684	22,000@-30°C	28,000@-20°C
Flash Point	°C	ASTM D92	215	220
Pour Point	°C	ASTM D97	-37	-30

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

Exceeds Performance Requirements

API SQ, API SP, API SN Plus, API SN

Product Codes

PFV-10W40, PFV-20W50

AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING

PROFLUID ENGINEERED BY PROFESSIONALS FOR PROFESSIONALS

10084 E. Kemper Rd, Suite 103,
Loveland, Ohio 45140 - (513) 987-4100

Learn More At www.PROFLUIDLLC.com
sales@profluidllc.com

Made in U.S.A