



## PF5™ Export Heavy Duty Synthetic Blend Heavy-Duty Engine Oils

SAE 15W-50, 20W-50; API CJ-4/SN

PF5™ Export Heavy Duty Synthetic Blend Heavy-Duty Engine Oils, SAE 15W-50 and SAE 20W-50, API CJ-4/SN are advanced parasyntetic crankcase lubricants specially engineered for use in today's high-performance diesel engines. These oils are formulated using a carefully balanced combination of synthetic and conventional base stocks, along with a premium additive system. This sophisticated formulation provides outstanding engine protection and performance even under the most demanding operating conditions.

Thanks to their advanced chemistry, these heavy-duty engine oils deliver:

- Superior detergency and dispersancy for cleaner engines and reduced sludge or deposit formation
- Exceptional anti-wear protection, helping to extend engine life and reduce maintenance costs
- Robust anti-corrosion capabilities to safeguard engine components in harsh environments
- Outstanding oxidation resistance, ensuring oil stability at high temperatures and longer drain intervals
- Effective anti-foaming properties for consistent oil pressure and lubrication

PF5™ Export Heavy Duty Synthetic Blend Heavy-Duty Engine Oils meet or exceed the requirements of the API CJ-4 and SN service categories, making them ideal for use in a wide range of modern diesel engines, including those equipped with advanced emission control systems. These oils help maintain optimal engine cleanliness and reliability, providing peace of mind for operators who demand maximum durability and protection from their equipment.

### Typical Properties

Physical	Unit	Test Method	15W-50	20W-50
Appearance, Visual	—	Visual	Amber, Transparent, Liquid	
Viscosity@40°C	cSt	ASTM D445	129.25	160.55
Viscosity@100°C	cSt	ASTM D445	17.5	18.5
Viscosity Index	—	ASTM D2270	150	130
CCS Apparent Viscosity	cP	ASTM D5293	6,300@-20°C	6,250@-15°C
Flash Point	°C	ASTM D92	220	225
Pour Point	°C	ASTM D97	-35	-30
Total Base Number	mg KOH/g	ASTM D2896	9	9

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

### Exceeds Performance Requirements

API CJ-4, CI-4 Plus, CI-4, CH-4, CF-4, CF-2, CF  
API SN, SM, SL, SJ, SG

### Product Codes

PF5EHD-15W50, PF5EHD-20W50

**AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING**



10084 E. Kemper Rd, Suite 103,  
Loveland, Ohio 45140 - (513) 987-4100

Learn More At [www.PROFLUIDLLC.com](http://www.PROFLUIDLLC.com)  
[sales@profluidllc.com](mailto:sales@profluidllc.com)

