

ProFluid™ Velocity SAE 5W-20, 5W-30, 10W-30

Synthetic Blend Motor Oil, API SQ, ILSAC GF-7A

ProFluid™ Velocity SAE 5W-20, 5W-30, and 10W-30 are advanced, premium-quality synthetic blend motor oils designed specifically for use in the latest gasoline-powered engines that call for ILSAC GF-7A, GF-6A, API SQ, API SP, API SN Plus, or API SN performance standards. These motor oils provide outstanding protection and efficiency for a wide range of passenger cars, SUVs, and light trucks, ensuring optimal engine performance under diverse driving conditions.

ProFluid™ Velocity oils are expertly blended from a combination of high-performance synthetic and Group II paraffinic base oils, together with an advanced additive system. This sophisticated formulation is specifically engineered to deliver exceptional protection for high-compression gasoline direct injection engines.

- Meets and exceeds industry requirements for modern engine designs, including turbocharged and direct injection systems
- Ensures excellent engine cleanliness and minimizes sludge formation, even under severe driving conditions
- Provides enhanced oxidative stability for longer oil life and sustained engine performance
- Improved low-speed pre-ignition (LSPI) protection, safeguarding engines from premature damage

ProFluid™ Velocity Motor Oils are an ideal choice for drivers seeking reliable, state-of-the-art lubrication that preserves engine efficiency, reduces emissions, and provides peace of mind through enhanced protection and performance.

Typical Properties

Physical	Unit	Test Method	5W-20	5W-30	10W-30
Appearance, Visual	—	Visual	Amber, Transparent, Liquid		
Viscosity@40°C	cSt	ASTM D445	48.95	62.8	70.7
Viscosity@100°C	cSt	ASTM D445	8.3	10.8	10.9
Viscosity Index	—	ASTM D2270	145	165	145
CCS Apparent Viscosity	cP	ASTM D5293	5,300@-30°C	5,800@-30°C	5,000@-25°C
MRV Apparent Viscosity	cP	ASTM D4684	18,000@-35°C	22,000@-35°C	15,000@-30°C
Flash Point	°C	ASTM D92	210	210	215
Pour Point	°C	ASTM D97	-43	-42	-40

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

Exceeds Performance Requirements

API SQ with Resource Conserving, API SP, API SN Plus, API SN
 ILSAC GF-7A, GF-6A, GF-5
 Chrysler MS6395
 Ford WSS-M2C970-A1 (5W-20); Ford WSS-M2C971-A1 (5W-30)

Product Codes

PFV-5W20-HM, PFV-5W30-HM, PFV-10W30

AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING