

ProFluid™ Velo-Elite Euro SAE 5W-30

Full Synthetic Motor Oil, ACEA C3, API SN

ProFluid™ Velo-Elite Euro SAE 5W-30 Full Synthetic Motor Oil ACEA C3, API SN is expertly engineered using advanced synthetic base oils combined with a high-quality additive package. Designed for exceptional performance, this motor oil is suitable for carbureted, fuel injected, turbocharged, and supercharged gasoline engines. It not only meets, but surpasses, industry performance standards, offering enhanced protection and reliability for modern vehicles.

- Provides robust protection for high compression gasoline direct injection engines
- Delivers excellent oxidative stability, helping to extend oil life and engine durability
- Controls engine deposits for cleaner operation and improved efficiency

ProFluid™ Velo-Elite products utilize synthetic base oils and advanced additive formulations that are specifically developed to safeguard high compression gasoline direct injection engines. These oils deliver outstanding oxidative stability, superior deposit control, effective mitigation of low speed pre-ignition, and reliable timing chain wear protection, ensuring optimal performance and longevity for your engine.

Typical Properties

Physical	Unit	Test Method	5W-30
Appearance, Visual	—	Visual	Amber, Transparent, Liquid
Viscosity @ 40°C	cSt	ASTM D445	68.0
Viscosity @ 100°C	cSt	ASTM D445	11.5
Viscosity Index	—	ASTM D2270	165
CCS Apparent Viscosity	cP	ASTM D5293	5,300@-30°C
MRV Apparent Viscosity	cP	ASTM D4684	22,000@-35°C
Flash Point	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-42
Sulfated Ash	wt%	ASTM D874	≤ 0.8

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

Exceeds Performance Requirements

ACEA C3-23
 API SN
 BMW LL-04
 MB 229.31/229.51
 GM dexos 2

Product Code

PFVE-5W30-EURO

AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING