

ProFluid™ Velo-Elite Euro SAE 5W-40

Full Synthetic Motor Oil, ACEA A3/B4, API SN

ProFluid™ Velo-Elite Euro SAE 5W-40 Full Synthetic Motor Oil ACEA A3/B4, API SN is crafted using high-quality synthetic base oils and an advanced additive blend. This motor oil is ideal for carbureted, fuel-injected, turbocharged, and supercharged gasoline engines, and it surpasses the performance standards outlined below.

- Formulated for both traditional and modern gasoline engines
- Helps prevent engine deposits and sludge buildup
- Improves engine longevity and performance
- Offers protection against timing chain wear and low-speed pre-ignition

ProFluid™ Velo-Elite products utilize synthetic base oils and premium additive packages specifically engineered to safeguard high-compression gasoline direct injection engines. They provide exceptional oxidative stability, effective deposit control, reduce the risk of low-speed pre-ignition, and protect timing chains from excessive wear.

Typical Properties

Physical	Unit	Test Method	5W-40
Appearance, Visual	—	Visual	Amber, Transparent, Liquid
Viscosity@40°C	cSt	ASTM D445	80.0
Viscosity@100°C	cSt	ASTM D445	13.5
Viscosity Index	—	ASTM D2270	172
CCS Apparent Viscosity	cP	ASTM D5293	5,600@-30°C
MRV Apparent Viscosity	cP	ASTM D4684	23,000@-35°C
Flash Point	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	10.5

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

Exceeds Performance Requirements

ACEA A3/B4-23
 ACEA A3/B3-16
 API SN/CF
 Porsche A40
 MB 226.5 / 229.3 / 229.5
 BMW LL-01
 VW 502.00, 505.00
 Renault RN0700 / RN0710

Product Code

PFVE-5W40-EURO

AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING