

ProFluid™ Velo-Elite SAE 5W-40, SAE 5W-50

Full Synthetic Motor Oil, API SQ

ProFluid™ Velo-Elite SAE 5W-40 and 5W-50 are advanced, full synthetic motor oils meticulously engineered for high-performance, modern gasoline engines. Meeting and surpassing demanding API SQ, API SP, API SN Plus, and API SN specifications, these lubricants offer exceptional reliability and safeguard critical engine components under a wide range of driving conditions.

ProFluid™ Velo-Elite oils utilize cutting-edge synthetic base stocks and a sophisticated additive package. This advanced formulation delivers robust protection for high-compression, gasoline direct injection engines, helping drivers maintain peak engine cleanliness and maximize performance. The oils are designed to extend engine longevity and reduce maintenance, making them an ideal choice for enthusiasts and daily drivers alike.

- Provides outstanding oxidative stability for extended oil life and consistent engine performance
- Enhances deposit control and mitigates low-speed pre-ignition for modern turbocharged applications
- Supports emission system compatibility by reducing sulfated ash levels

Choose ProFluid™ Velo-Elite for reliable cold-start protection, improved wear resistance, and the confidence that comes with advanced, forward-thinking lubrication technology.

Typical Properties

Physical	Unit	Test Method	5W-40	5W-50
Appearance, Visual	—		Visual	Amber, Transparent, Liquid
Viscosity @ 40°C	cSt	ASTM D445	86.8	115
Viscosity @ 100°C	cSt	ASTM D445	14.5	18.5
Viscosity Index	—	ASTM D2270	175	180
CCS Apparent Viscosity	cP	ASTM D5293	5,400@-30°C	5,800@-30°C
MRV Apparent Viscosity	cP	ASTM D4684	22,000@-35°C	23,000@-35°C
Flash Point	°C	ASTM D92	215	215
Pour Point	°C	ASTM D97	-42	-42

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

Exceeds Performance Requirements

API SQ, API SP, API SN Plus, API SN

Product Codes

PFVE-5W40, PFVE-5W50

AVAILABLE VIA RAILCARS, TRUCKS, TOTES, DRUMS, PAILS, AND SMALLER PACKAGING